



SC05MV0

| | | |
|------------------------------|---------------------|----------|
| Capacity trays | 5 GN1/1 - 5 600x400 | |
| Distance between trays (mm) | 74 | |
| Frequency (Hz) | 50 | |
| Voltage | A | 230V 1 N |
| | B | NO |
| | C | NO |
| | D | NO |
| Power (kW) + (V/Kw) | 0,3 + 9,5 | |
| Oven size (WxDxH mm) | 870 X 786 X 719 | |
| Max cooking temperature (°C) | 280 | |
| Oven weigh (Kg) | 120 | |

FEATURES

◆ Standard | ◇ Optional | - Not available

MANUAL COOKING

| | | |
|------------------------------------|--------------|---|
| Convection cooking | 30°C - 280°C | ◆ |
| Mixed steam and convection cooking | 30°C - 230°C | ◆ |
| Steaming | 35°C - 130°C | ◆ |
| Dry air cooking | 30°C - 280°C | ◆ |
| Delta T cooking with core probe | | - |
| With core probe | | ◇ |
| Low temperature cooking | | ◆ |
| Sous Vide cooking | | - |

SPECIAL CYCLES

| | | |
|-------------------------|--|---|
| Multi-level mix: | | - |
| Core probe regeneration | | - |
| Timed regeneration | | ◆ |

V-OVERNIGHT COOKING

| | | |
|---------------------|--|---|
| V-COOK & HOLD | | - |
| Multi-timer cooking | | - |
| Proofing | | - |
| Automatic Cooling | | - |

V-SELF CLEANING SYSTEM

| | | |
|------------------|--|---|
| V-RINSING SYSTEM | | - |
|------------------|--|---|

AUTOMATIC COOKING

| | | |
|----------------------------------------------------------------|--|---|
| V-RECIPE BOOK | | - |
| Program: possibility to memorize program with name and picture | | - |
| Overnight automatic cleaning program | | - |
| Automatic pre-heating setting | | - |
| Programmable timers | | - |
| Cooking cycles for each program | | - |

AIR DISTRIBUTION IN THE COOKING CHAMBER

| | | |
|-------------------------------|---|---|
| V-BI.DIRETIONAL REVERSING FAN | | ◆ |
| Number of speed regulation | 2 | |

OVERLAP SYSTEM

| | | |
|---------------------------------------------------|--|---|
| V- OVERLAP CONNECTION with ovens | | ◇ |
| V- OVERLAP CONNECTION with Venix's Blast Chillers | | - |
| V- OVERLAP CONNECTION with Venix's Proofing | | ◇ |
| V- OVERLAP CONNECTION with Venix's Stand | | ◇ |

| OTHER FUNCTIONS | | |
|-----------------------------------------------------|-----|---|
| Infinity time | | ◆ |
| Multilangue software | | - |
| Temperature parameter unit F° or C° | | ◇ |
| Gas reset | | ◆ |
| V - LIGHTS | LED | ◆ |
| Lights integrated in the door | | ◆ |
| CONNECTION | | |
| USB | | - |
| WI-FI | | - |
| VENIX-CLOUD | | - |
| TECHNICAL DETAILS | | |
| Internal glass easy clean system | | ◆ |
| V- BREAK DROP technology for excellent humidity | | ◆ |
| Thermal insulation structure (energetic efficiency) | | ◆ |
| Inverter technology | | - |
| External connection for 2nd core probe | | - |
| Digital water injection regulation | | ◆ |