



## CP043M0N0

BAKERY OVEN 4 TRAYS 460 x 340 - GN 2/3\*  
MECHANICAL CONTROL

\*Optional tray rack support for GN 2/3



## FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Electric
Timer	Linear scale
Number of motors	1
Motor speeds	1 speed + reverse rotation
Max cooking temperature	260 °C
Core probe	-
Cooking chamber material	AISI 430
Opening door	Right handle
Chimney	20 mm open
Humidification	Direct injection
Air Injection	-
Version	Standard

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Wire PA 4/75 mm
Max tray load	3 Kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	614x767x602 mm
Oven size without handle WxDxH (mm)	614x703x602 mm
Chamber size WxDxH (mm)	494x408x345 mm
Unit weight (kg)	43,8 kg

## PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH	640x810x733 mm
Unit weight with packaging	56,4Kg

## ELECTRICAL DATA

### HEATERS 3.1kW 50/60Hz

Power	3,4kW
Frequency	50/60Hz
Power supply	220-240V ~
Amperage	14,8A
Power cord req.	3G1,5

## WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	-
Water drain	-
Max water hardness	5 [° f]
Water pressure requirement min-max	150-200 kPa

## CONSUMPTION

Humidification Water with solenoid valve	3,9 [l/h] max consumption
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

## CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

## ACCESSORIES

Self clean system kit	S1
Oven stand	-
Stand wheel kit	R60B
Hood (Air)	-
Hood (Water)	POCK
External Core probe	-
Sous vide probe	-
Core Probe	-
Proofer	-
Stacking kit for 2 ovens	SKCP43N00
Smoker	-
Bast Chiller	-
Blast chiller stacking kit	-

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 6 Kg	-
Detergent 10 Kg	-