



## SQ0621AMVNO

COMBI GAS OVEN 6 - GN 2/1 - 12 - GN 1/1  
or 6 - 660X460 \*  
MECHANICAL CONTROL

\*Special tray rack support on request



## FUNCTIONAL CHARACTERISTICS

Display	Analogic
Supply	Natural gas / GPL
Timer	Linear
Number of motors	2
Motor speeds	2
Max cooking temperature (°C)	260 [°C] 500 [°F]
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 [mm] open 2 [inch] open
Humidification	Direct Injection
Air Injection	-
Version	Standard

## STANDARDS

Certification	CB/GAR
---------------	--------

## TRAYS

Trays rack	Sheet GA-BIV 6/80 [mm] Sheet GA-BIV 6/3,14 [inch]
Max tray load	4 [kg] 9 [lb]

## DIMENSIONS

Oven size with handle WxDxH (mm)	964x1208x985 [mm] 37,6x47,6x38,8 [inch]
Oven size without handle WxDxH (mm)	964x1143x985 [mm] 38x45x38,8 [inch]
Chamber size WxDxH (mm)	660x770x612 [mm] 26x30,3x24,1 [inch]
Unit weight (Kg)	129 [kg] 284 [lb]

## PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1055x1245x1082 [mm] 41,5x49x42,6 [inch]
Unit weight with packaging (Kg)	150 [kg] 330 [lb]
Crate packaging size (optional)	-

## ELECTRICAL DATA

50Hz	
Power	0,4 kW
Frequency	50Hz
Power supply	220-240V 1N~
Amperage	1,82A
Power cord req.	3G1,5
60Hz	
Power	0,54 kW
Frequency	60Hz
Power supply	220-240V 1N~
Amperage	2,45A
Power cord req.	3G1,5

## BURNER DATA

G30-G31 Power (kW)	15 [kW] 51182 [btu/h]
G20 Power (kW)	15 [kW] 51182 [btu/h]

## WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	8 [mm] quick fitting
Water drain	30 [mm] 1,2 [inch]
Max water hardness	5 [°f]
Water pressure requirement min-max	150-200 [kPa] 22-29 [psi]

## CONSUMPTION

Humidification Water (L/h)	22,4 [l/h] max consumption 5,9 [gal/h] max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

<b>CONNECTIVITY</b>	
USB	USB 2.0
Bluetooth	-
Wi-Fi	Yes
Cloud	Yes
<b>ACCESSORIES</b>	
Nozzle kit	85BRU00018 (Gas02)
Self clean system kit	-
Oven stand	-
Hood (Air)	-
Hood (Water)	-
External Core probe	-
Sous vide probe	-
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4