



CA8212M0

CANNAREGIO PROOFER
FOR CAMPIELLO OVENS
6 TRAYS GN 2/1 - 600X400 - 12 TRAYS GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Overlapping oven	CP04*-CP05* CP06*-CP07* CP10*-CP12*
Display	ANALOGIC
Supply	ELECTRIC
Timer	-
Max proofing temperature (°C)	60°C
Core probe	-
Cooking chamber material	AISI430
Opening door	Double door

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet PA-BIV 6/75
Max tray load	4kg

DIMENSIONS

Size with handle WxDxH (mm)	820x890x705
Chamber size WxDxH (mm)	610x810x560
Unit weight (Kg)	48

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	875x980x820
Unit weight with packaging (Kg)	62,8
Crate packaging size (optional)	-

ELECTRICAL DATA

HEATERS 1,3 kW (50/60 Hz)	
Power	2,4kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	10,4A
Power cord req.	3G1,5



WATER CONNECTION REQUIREMENTS

Humidification Water inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA

