



SG04M0G0

BAKERY OVEN 4 TRAYS 600 X 400 - GN 1/1
MECHANICAL CONTROL
LOGARITHMIC SCALE



FUNCTIONAL CHARACTERISTICS

Display	ANALOGIC
Supply	ELECTRIC
Timer	LOGARITHMIC
Number of motors	1
Motor speeds	1
Max cooking temperature (°C)	260°
Core probe	-
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm Manual valve

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet PA-BIV 4/80 Sheet PA-BIV 5/75 Trolley rails
Max tray load	4kg

DIMENSIONS

Oven size with handle WxDxH (mm)	792 x 1029 x 781
Oven size without handle WxDxH (mm)	793 x 962 x 781
Chamber size WxDxH (mm)	460 x 630 x 452
Unit weight (Kg)	92

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	880 x 1110 x 956
Unit weight with packaging (Kg)	112
Crate packaging size (optional)	880 X 1110 X 960

ELECTRICAL DATA

HEATERS 9kW 50Hz	
Power	9,3kW
Frequency	50Hz
Power supply	380-415V 3N~/220-240V 3~
Amperage	14,3A / 23,6A
Power cord req.	5G1,5/ 4G4



WATER CONNECTION REQUIREMENTS

Humidification / Washing Water Inlet	3,4" GAS
Water drain	50 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water (L/h)	3,9l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	-
Bluetooth	-
Ethernet RJ45	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	TA7984H17X TA7984H30X TA7984H40S-TA7984H40X TA7984H49S-TA7984H49X TA7984H70S-TA7984H70X TA7984H80S-TA7984H80X
Hood (Air)	POSGMAF1 POSGMAF2
Hood (Water)	POSGMWF1 POSGMWF2
External Core Probe	-
Sous Vide Core Probe	-
Proofer	CA7912
Stacking kit for 2 ovens	SKSG15 SKSG85
Smoker	SMK02
Blast Chiller	ASP05



Blast chiller stacking kit	SK16
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	-
Detergent10KG	-

