



SQ05ADG0

GAS COMBI OVEN 5 TRAYS - GN 1/1
2,4" DIGITAL LCD CONTROL



FUNCTIONAL CHARACTERISTICS

Display	2,4" LCD IPS
Supply	Natural gas / GPL
Timer	-
Number of motors	1
Motor speeds	2
Max cooking temperature (°C)	260 °C
Core probe	Single point PT1000 (optional)
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm open
Humidification	Direct Injection
Air Injection	-
Version	Standard

STANDARDS

Certification	CE-GAR-CB
---------------	-----------

TRAYS

Trays rack	Wire GA 5/70 mm
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	939x933x821
Oven size without handle WxDxH (mm)	939x868x821
Chamber size WxDxH (mm)	660x486x488
Unit weight (Kg)	117

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1020 x 970 x 912
Unit weight with packaging (Kg)	137
Crate packaging size (optional)	-

ELECTRICAL DATA

50Hz	
Power	0,22 kW
Frequency	50Hz



Power supply	220-240V 1N~
Amperage	1A
Power cord req.	3G1,5
60Hz	
Power	0,29 kW
Frequency	60Hz
Power supply	220-240V 1N~
Amperage	1,32A
Power cord req.	3G1,5
BURNER DATA	
G30-G31 POWER (KW)	12
G20 POWER (KW)	12
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	8 mm quick fitting
Water drain	30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa
CONSUMPTION	
Humidification Water (L/h)	23,6l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-
CONNECTIVITY	
USB	USB 2.0
Bluetooth	-
Wi-Fi	Yes
Cloud	Yes
ACCESSORIES	
Nozzle kit	85BRU00017 (GAS01)
Self clean system kit	-



Oven stand	TA9374H30X TA9374H40X-TA9374H40S TA9374H49X-TA9374H49S TA9374H70X-TA9374H70S TA9374H80X-TA9374H80S
Hood (Air)	-
Hood (Water)	-
External Core probe	CP5 (020SON0007)
Sous vide probe	CP4 (020SON0010)
Proofer	CA9308M0 CA9308MH CA9308DH CA9312M0 CA9312MH CA9312DH
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast chiller	KDA03 KDA05
Blast chiller stacking kit	SK43
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

