



## SQ16D00

BAKERY OVEN 16 TRAYS 600x400 GN 1/1  
DIGITAL CONTROL



## FUNCTIONAL CHARACTERISTICS

Display	DIGITAL + ENCODER
Supply	ELECTRIC
Timer	-
Number of motors	4
Motor speeds	2
Max cooking temperature (°C)	260°C
Core probe	Single point TCJ (Optional)
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm motorized
Humidification	Direct injection
Air injection	-
Self-washing	-

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Trolley PA 16/80
Max tray load	4 kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	1051 X 1002 X 1900
Oven size without handle WxDxH (mm)	1051 X 938 X 1900
Chamber size WxDxH (mm)	700 X 481 X 1496
Unit weight (Kg)	250

## PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	1150 X 1100 X 2050
Unit weight with packaging (Kg)	273
Crate packaging size (optional)	1020 X 970 X 1370



## ELECTRICAL DATA

### HEATERS 6,75kW 50Hz - Single power supply

Power	28,1kW
Frequency	50Hz
Power supply (standard)	380-415V 3N~
Amperage (standard)	43,9A
Power cord req. (standard)	5G10

### HEATERS 6,75kW 50Hz - Double power supply

Power	28,1kW
Frequency	50Hz
Power supply (optional)	380-415V 3N~/220-240V 3~
Amperage (optional)	43,9A/71,9A
Power cord req. (optional)	5G10/4G25

### HEATERS 6,75kW 60Hz - Single power supply

Power	28,7kW
Frequency	60Hz
Power supply (standard)	380-415V 3N~
Amperage (standard)	46,5A
Power cord req. (standard)	5G10

### HEATERS 6,75kW 60Hz - Double power supply

Power	28,7kW
Frequency	60Hz
Power supply (optional)	380-415V 3N~/220-240V 3~
Amperage (optional)	46,5A/74,1A
Power cord req. (optional)	5G10/4G25

## WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" GAS
Washing Water Inlet	-
Water drain	2 x 30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa



## CONSUMPTION

Humidification Water (L/h)	16,1l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

## CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

## ACCESSORIES

Self clean system kit	S17
Oven stand	-
Hood (Air)	-
Hood (Water)	POSLMWF1 POSLMWF2
Core Probe	CP1 (020SON0003)
Proofer	-
Stacking kit for 2 ovens	-
Smoker	SMK02
Blast Chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

