



VE03LTDAERO

3 TRAYS 600 X 400 - GN 1/1



FUNCTIONAL CHARACTERISTICS

Display	LCD 2,4" IPS
Supply	Electric
Timer	-
Number of motors	1
Motor speeds	5
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap Door
Chimney	30mm open
Humidification	Direct injection
Air injection	V-Dry
Self-washing	-

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	3x PA-BIV 3/80
Max tray load	4kg

DIMENSIONS

Oven size with handle WxDxH (mm)	800x840x460
Oven size without handle WxDxH (mm)	800x800x460
Chamber size WxDxH (mm)	695x465x265
Unit weight (kg)	52 kg

PACKAGING

Packaging	Pallet + Carton Box
Packaging size WxDxH (mm)	855x850x615
Unit weight with packaging (Kg)	62 kg

ELECTRICAL DATA

HEATERS 3,1kW (50/60Hz)	
Power	3,4kW
Frequency	50/60Hz
Power supply	230V 1~



Amperage	15A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	3/4" M Gas threaded
Washing Water inlet	-
Water drain	-
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water	0-2,4 l/h
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

ACCESSORIES

Oven stand	TA8058H60X - TA8058H60S TA8058H80X - TA8058H80S
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	-
Core probe	-
Proofers	CA8008M0 CA8008MH CA8008DH
Stacking kit for 2 ovens	SK51
Smoker	SMK02
Blast chiller	-
Blast chiller stacking kit	-



Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 6KG	-
Detergent 10KG	-

