



VE043LTHAERO

4 TRAYS 460 X 340 / GN 2/3*

*Special tray rack support on request



FUNCTIONAL CHARACTERISTICS

Display	LCD 2,4" IPS
Supply	Electric
Timer	-
Number of motors	1
Motor speeds	5
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap Door
Chimney	30mm open
Humidification	Direct injection
Air injection	-
Self-washing	-

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	4 x PA WIRE 4/80 (460X340) OPT 4 x GA-BIV 4/80 GN2/3 PA 460X340
Max tray load	4kg

DIMENSIONS

Oven size with handle WxDxH (mm)	600x770x540
Oven size without handle WxDxH (mm)	600x730x540
Chamber size WxDxH (mm)	495x420x345
Unit weight (kg)	50 kg

PACKAGING

Packaging	Pallet + Carton box
Packaging size WxDxH (mm)	675x825x692
Unit weight with packaging (Kg)	60 kg

ELECTRICAL DATA

HEATERS 3,1kW (50/60Hz)	
Power	3,4kW
Frequency	50/60Hz



Power supply	230V 1~
Amperage	15A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	3/4" M Gas threaded
Washing Water inlet	8mm quick fitting
Water drain	-
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Humidification Water	0-2,4 l/h
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

ACCESSORIES

Oven stand	TA6054H80S-TA6054H80X TA6054H60S-TA6054H60X
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	-
Core probe	-
Proofers	CA6008M0 CA6008MH CA6008DH
Stacking kit for 2 ovens	SK52
Smoker	SMK02
Blast chiller	-
Blast chiller stacking kit	-



Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent 10KG	DT4

