



SQDK01DGBD03S

SQUERO DECK OVEN
1 X PA 600 X 400
2,4" DIGITAL LCD CONTROL
AISI 304 STAINLESS STEEL SOLE



FUNCTIONAL CHARACTERISTICS

Display	LCD
Supply	ELECTRICAL
Cooking type	STATIC
Max cooking temperature	400 °C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap door
Sole	AISI 304
Chimney	50 mm motorized
Boiler	Boiler
Air injection	V-dry

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	1x PA 600x400
Max tray load	5 kg

DIMENSIONS

Unit size with handle WxDxH	937 x 907 x 447 mm
Unit size without handle WxDxH	937 x 860 x 447 mm
Chamber size WxDxH	620 x 535 x 225 mm
Unit weight	71,6 kg

PACKAGING

Packaging	Pallet + Carton Box
Packaging size WxDxH	985 x 950 x 560 mm
Unit weight with packaging	84.4 kg
Crate packaging size (optional)	985x950x572

ELECTRICAL DATA

Power	3,3kW
Frequency	50/60Hz
Power supply	220-240V 1~
Amperage	14,4A
Power cord req.	3G1,5



WATER CONNECTION REQUIREMENTS

Humidification Water inlet	3/4" M Gas threaded
Max water hardness	5 °f
Water pressure requirement min-max	150-200 kPa

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	STANDARD
Cloud	STANDARD

ACCESSORIES

Oven stand	TA9374H30X TA9374H40X-TA9374H40S TA9374H49X-TA9374H49S TA9374H70X-TA9374H70S TA9374H80X-TA9374H80S
Proofer	CA9308M0 CA9308MH CA9308DH
Stacking kit for 2 ovens	SKDK01
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA

