



SQDK02DGBD03R

SQUERO DECK OVEN
2 X PA 600 X 400
2,4" DIGITAL LCD CONTROL
REFRACTORY STONE



FUNCTIONAL CHARACTERISTICS

Display	LCD
Supply	ELECTRICAL
Cooking type	STATIC
Max cooking temperature	400 °C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap door
Sole	Single slab refractory stone
Chimney	50 mm motorized
Boiler	Boiler
Air injection	V-dry

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	2 x PA 600x400
Max tray load	5 kg

DIMENSIONS

Unit size with handle WxDxH	937 x 1207 x 447 mm
Unit size without handle WxDxH	937 x 1160 x 447 mm
Chamber size WxDxH	606 x 941 x 225 mm
Unit weight	81,6 kg

PACKAGING

Packaging	Pallet + Carton Box
Packaging size WxDxH	985 x 1245 x 560 mm
Unit weight with packaging	129,2 kg
Crate packaging size	-

ELECTRICAL DATA

Heaters 425W	
Power	6,1kW
Frequency	50/60Hz
Power supply	380-415V 3N~ / 220-240V 3~ / 220-240V 1N~
Amperage	10,1A / 16A / 26,5A
Power cord req.	5G1,5 / 4G2,5 / 3G4



WATER CONNECTION REQUIREMENTS

Humidification Water inlet	3/4" M Gas threaded
Max water hardness	5 °f
Water pressure requirement min-max	150-200 kPa

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	STANDARD
Cloud	STANDARD

ACCESSORIES

Oven stand	TA9374H30X TA9374H40X-TA9374H40S TA9374H49X-TA9374H49S TA9374H70X-TA9374H70S TA9374H80X-TA9374H80S
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA

