



SPZLROHERO

HIGH-SPEED CONVECTION OVEN
2,4" LCD DIGITAL CONTROL

PIZZA PADDLE, PANINI PADDLE, PIZZA GRID, PANINI GRID, OVEN TRAY,
TEFLON SHEET, TEFLON TRAY INCLUDED



FUNCTIONAL CHARACTERISTICS

Display	DIGITAL
Supply	ELECTRIC
Timer	-
Number of motors	1
Motor speeds	5 speed + inverter
Max cooking temperature	260 °C
Probe	Single point PT1000
Cooking chamber material	AISI 430
Opening door	Flap door
Chimney	20 mm open
Humidification	-
Air Injection	-
Version	Standard

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	sheet metal single level
Max tray load	3 Kg

DIMENSIONS

Oven size with handle WxDxH	460 x 655 x 525 mm
Oven size without handle WxDxH	460 x 610 x 525 mm
Chamber size WxDxH	320 x 315 x 215 mm
Unit weight	40.4 kg

PACKAGING

Packaging	CARTON BOX
Packaging size WxDxH	544 x 694 x 570 mm
Unit weight with packaging	48.4 kg
Crate packaging size (optional)	510 x 720 x 670 mm
Unit weight with crate packaging (optional)	61.8 kg

ELECTRICAL DATA

Heaters 3,1 kW (50/60 Hz)	
Power	3,4kW
Frequency	50/60 Hz



Power supply	220-240V ~
Amperage	14,8A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	-
Washing Water inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

CONSUMPTION

Humidification Water with solenoid valve	-
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	USB 2.0
Bluetooth	
Wi-Fi	STANDARD
Cloud	STANDARD

ACCESSORIES

Pizza paddle	SPZFLA (1 included)
Panini paddle	SPZSHO (1 included)
Pizza grid	85GRI00327 (1 included)
Panini grid	85GRI00310 (1 included)
Teflon sheet	50GPP00086 (1 included)
Teflon tray	50GPP00087 (1 included)
Oven tray	85VAS00080 (1 included)
Control simulator	85KIT00167

