



POUSMDF2

DOUBLE CHIMNEY ENTRANCE

FUNCTIONAL CHARACTERISTICS

Control	Analogic
Condenser	Water
Filter	Grease Filter + Carbon filter
Supply	Electric
Number of motors	1
Motor speeds	2
Oven compatibility	SQ0621 - SQ1021

STANDARDS

Certification	CE
---------------	----



DIMENSIONS

Hood size WxDxH (mm)	960x872x320 mm
Unit weight (kg)	31,5 kg

PACKAGING

Packaging	CARTON BOX
Packaging size WxDxH (mm)	1030x960x496 mm
Unit weight with packaging (Kg)	43,4 kg

ELECTRICAL DATA

Power	0,34kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	1,5A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" Gas M Threaded
Water drain	30 mm
Max water hardness	5 °f
Water pressure requirement min-max	150-200 kPa

CONSUMPTION

Eco mode water consumption	0 - 0,44 l/m
Power mode water consumption	0 - 0,89 l/m

ACCESSORIES

Spare carbon filter cartridge	60FIL003 (2X)
Spare carbon filter kit	85FIL00006

