



## SQ0621DG0

COMBI OVEN 6 TRAYS - GN 2/1 /  
12 TRAYS - GN 1/1 OR 10 - 660X460\*  
2,4" DIGITAL LCD CONTROL

\*Special tray rack support on request



## FUNCTIONAL CHARACTERISTICS

Display	2,4" LCD IPS
Supply	Electric
Timer	-
Number of motors	2
Motor speeds	5
Max cooking temperature (°C)	260 °C
Core probe	Single point PT1000 (optional)
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm open
Humidification	Direct Injection
Air Injection	-
Version	Standard

## STANDARDS

Certification	CE
---------------	----

## TRAYS

Trays rack	Sheet 6/85 mm (GN1/1 / full pan)
Max tray load	8 kg

## DIMENSIONS

Oven size with handle WxDxH (mm)	960x1110x876 mm
Oven size without handle WxDxH (mm)	960x1045x876 mm
Chamber size WxDxH (mm)	660x788x612 mm
Unit weight (Kg)	167

## PACKAGING

Packaging	Pallet + carton box
Packaging size WxDxH (mm)	1050x1185x1085
Unit weight with packaging (Kg)	185
Packaging	Pallet + carton box + wood cage
Packaging size WxDxH (mm)	1098x1233x1108 mm



## ELECTRICAL DATA

### HEATERS 6,5kW 50/60Hz

Power	12,5kW
Frequency	50/60Hz
Power supply	380-415V 3N~
Amperage	19,8A
Power cord req.	5G4

## WATER CONNECTION REQUIREMENTS

Humidification Water Inlet	3/4" M Gas threaded
Washing Water Inlet	-
Water drain	30 mm
Max water hardness	5 °f
Water pressure requirement min-max	150-200 kPa

## CONSUMPTION

Humidification Water (L/h)	23,6l/h max consumption
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

## CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard

## ACCESSORIES

Self clean system kit	
Oven stand	TA9605H17X TA9605H30X TA9605H40X - TA9605H40S TA9605H49X - TA9605H49S TA9605H70X - TA9605H70S TA9605H80X - TA9605H80S



Wheels kit for stand	-
Hood (Air)	POUSMAF1 POUSMAF2
Hood (Water)	POUSMWF1 POUSMWF2 POUSMDF1 POUSMDF2
External Core probe	CP5 (020SON0007)
Sous vide probe	CP4 (020SON0010)
Proofers	-
Stacking kit for 2 ovens	SKS21EN00 SKS21EA00 SKS21EW00
Smoker	SMK02
Blast chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6 Kg	DT2
Detergent 10 Kg	DT4

